

SPECIFICATIONS

FULLTECH ELECTRIC CO.,LTD

MODEL	UF-12A23-L
ITEM	
RATED VOLTAGE	AC 230V
VOLTAGE RANGE	AC207-253V
SPEED(RPM)	50Hz 2100 RPM $\pm 10\%$ 60Hz 2300 RPM $\pm 10\%$
RATED CURRENT	50Hz 0.08 A $\pm 10\%$ 60Hz 0.07 A $\pm 10\%$
RATED INPUT	50Hz 17 W $\pm 10\%$ 60Hz 15 W $\pm 10\%$
LOCKED CURRENT	50Hz 0.09 A $\pm 10\%$ 60Hz 0.08 A $\pm 10\%$
MAX.AIR VOLUME	50Hz 75 $\pm 10\%$ CFM 60Hz 82 $\pm 10\%$ CFM
MAX.STATIC PRESSURE	50Hz 0.16 $\pm 10\%$ inH2O 60Hz 0.16 $\pm 10\%$ inH2O
OPERATING TEMP.	-40 °C~+70°C
STORAGE TEMP.	-40°C~+80°C
ROTATING DIRECTION	CLOCKWISE DIRECTION
BLOWING DIRECTION	EXHAUST OVER STRUTS
INSULATION RESISTANCE	DC 500 V 100M
DIELECTIC STRENGTH	AC 1500V / 1MIN.
NOISE	50Hz 36 dB 60Hz 38 dB
SAFETY PROTECTION	IMPEDANCE PROTECTION
INSULATION GRADE	CLASS B
BEARING	BALL BEARING
LIFE EXPECTANCY	OVER 40000 HOURS (40 °C)
FRAME MATERIAL	ALUMINUM (ADC-12)
IMPELLER	PLASTIC 94V-0 PBT. COVERING GLASS FIBER
DIMENSION	120*120*38 mm
WEIGHT	0.53 K GS.